

## IN THE CLAIMS

Please replace any previous listing of the claims with the following replacement listing of the claims:

### Replacement Listing of the Claims

1. (Currently amended) A method for tracing a denial-of-service attack on a victim machine back towards its source, comprising steps of:

operating a traceback program on at least one path to receive two input parameters, (a) an IP address (v) of the victim machine and (b) an IP address (r) of a router that is immediately upstream of the victim machine;

determining a set of routers that are neighbors (n) of r;

for each neighbor n of r, determining if r is n's next-hop for traffic addressed to v, or to a network that v is on, where node n's next-hop for traffic addressed to v is the IP address of the node that n will forward a packet to if the destination address in the packet is v;

if r is not n's next-hop for traffic addressed to v, skip over n and query the next neighbor of r, while if r is n's next-hop for traffic addressed to v, determining an amount of traffic that n is forwarding to r that is addressed to v; and

after based on the determined amounts of traffic of said neighbors,

determining the identity of the neighbor n of r that is the principal source of packets flowing to r that are addressed to v;<sub>i</sub>

continuing one node further upstream from the determined neighbor  $n$  of  $r$  that is the principal source of packets flowing to  $r$  that are addressed to  $v_{r,i}$  and

continuing to traceback through interconnected routers until a source of denial-of-service attack packets to  $v$  is determined or until further traceback is not possible.

2. (Original) A method as in claim 1, wherein the step of determining the set of neighbors comprises a step of sending at least one query to  $r$  to obtain information from a MIB that stores IP addresses of routers that are neighbors of  $r$ .

3. (Original) A method as in claim 1, wherein the step of determining if  $r$  is  $n$ 's next-hop for traffic addressed to  $v$  comprises a step of sending at least one query to router  $n$ .

4. (Original) A method as in claim 3, wherein the step of sending at least one query queries an IP Forwarding Table MIB of router  $n$ .

5. (Original) A method as in claim 1, wherein the step of determining an amount of traffic comprises a step of sending at least one message to a neighbor router  $n$  for determining a count of packets that router  $n$  is sending to router  $r$  that are addressed to  $v$  or to a network on which  $v$  resides.

6. (Original) A method as in claim 1, and further comprising a step of establishing a black hole host route to  $v$  as close as is possible to the source of the denial-of-service attack packets.

7. (Original) A method as in claim 1, and further comprising a step of establishing a special host route to  $v$  using the same next hop as an existing

route, the special host route tracking changes in the existing route such that when a next hop for the existing route changes, the next hop for the host route changes similarly.

8. (Original) A method as in claim 1, and further comprising a step of establishing a rate-limit for packets addressed to v as close as is possible to the source of the denial-of-service attack packets.

9. (Currently amended) A backtracking unit for tracing a denial-of-service attack on a victim machine back towards its source or sources, comprising a data processor responsive to a traceback computer program stored on a computer-readable media for receiving a first input parameter of an IP address (v) of the victim machine and a second input parameter of an IP address (r) of a router that is immediately upstream of the victim machine, said traceback computer program controlling operation of said data processor to determine a set of routers that are neighbors (n) of r and, for each neighbor n of r, to determine if r is n's next-hop for traffic addressed to v, where node n's next-hop for traffic addressed to v is the IP address of the node that n will forward a packet to if the destination address in the packet is v, said traceback computer program further controlling operation of said data processor for the case where r is not n's next-hop for traffic addressed to v, to skip over n and to query the next neighbor of r, while for the case where r is n's next-hop for traffic addressed to v, to determine an amount of traffic that n is forwarding to r that is addressed to v, and after-based on the determined amounts of traffic of said neighbors, determining the identity of the neighbor n of r that is the principal source of packets flowing to r that are addressed to v or to a network to which v is connected, for continuing further upstream from the determined neighbor n of r that is the principal source of packets flowing to r that are addressed to v to continue to traceback through interconnected routers until a source of denial-of-service attack packets to v is determined, or until further traceback is not possible.

10. (Original) A backtracking unit as in claim 9, wherein said data processor operates to send at least one query to *r* to obtain information from a MIB that stores IP addresses of routers that are neighbors of *r*.

11. (Original) A backtracking unit as in claim 9, wherein said data processor operates to send at least one query to an IP Forwarding Table MIB of router *n*.

12. (Original) A backtracking unit as in claim 9, wherein said data processor, while determining an amount of traffic that *n* is forwarding to *r* that is addressed to *v*, operates under control of said traceback computer program to send at least one message to at least one neighbor router *n* to determine a count of packets that router *n* is sending to router *r* that are addressed to *v* or to the network to which *v* is connected.

13. (Original) A backtracking unit as in claim 9, wherein said data processor further operates to establish a black hole host route to *v* as close as is possible to the source of the denial-of-service attack packets.

14. (Original) A backtracking unit as in claim 9, wherein said data processor further operates to establish a special host route to *v* using the same next hop as an existing route, the special host route tracking changes in the existing route such that when a next hop for the existing route changes, the next hop for the host route changes similarly.

15. (Original) A backtracking unit as in claim 9, wherein said data processor further operates to establish a rate-limit for packets addressed to *v* as close as is possible to the source of the denial-of-service attack packets.

16. (Previously presented) A method for determining an identity of a source of undesirable packets received from a data communications network, comprising steps of:

operating a traceback function to receive at least one input parameter, namely a network address (v) of a first device receiving the undesirable packets;

determining a set of network routers that are neighbors (n) of a network router (r) that is coupled to a second device immediately upstream of the first device; and

querying individual ones of packet routers in order to determine a packet router that is a largest source of packets addressed to v via r, or to a network to which v is connected, and continuing to query packet routers up through a hierarchy of interconnected packet routers until an identity of a source of the undesirable packets is discovered or until further backtracking is not possible.

17. (Original) A method as in claim 16, wherein the steps of determining and querying each comprise a step of sending queries to the data communications network.

18. (Original) A method as in claim 16, wherein the step of querying comprises steps of:

sending a first network message to a packet router for instructing the packet router to determine a number of packets that it is sending addressed to v; and

sending a second network message to the packet router to query the packet router for the determined number.

19. (Original) A method as in claim 16, wherein the step of querying comprises a step of sending at least one message to a packet router for determining a number of packets being forwarded to or towards v.

20. (Original) A method as in claim 16, and further comprising a step of establishing at least one of a black hole host route to v as close as is possible to the source of the undesirable packets, establishing a special host route to v using the same next hop as an existing route, the special host route tracking changes in the existing route such that when a next hop for the existing route changes, the next hop for the host route changes similarly, and establishing a rate-limit for packets addressed to v as close as is possible to the source of the denial-of-service attack packets.

21. (Original) A method as in claim 16, wherein the step of operating the traceback function operates the traceback function on a plurality of selected paths, wherein a particular path is selected based at least on an amount of traffic flowing through the path.

22. (Currently amended) A method for tracing a denial-of-service attack on a victim machine back towards its source, comprising steps of:

operating a traceback program on at least one path to receive two input parameters, (a) an IP address (v) of the victim machine and (b) an IP address (r) of a router that is immediately upstream of the victim machine;

determining a set of routers that are neighbors (n) of r;

for each neighbor n of r, determining if r is n's next-hop for traffic addressed to v, or to a network that v is on, where node n's next-hop for traffic addressed to v is the IP address of the node that n will forward a packet to if the destination address in the packet is v;

if r is not n's next-hop for traffic addressed to v, skip over n and query the next neighbor of r, while if r is n's next-hop for traffic addressed to v, determining an amount of traffic that n is forwarding to r that is addressed to v by sending at least one message to a neighbor router n for determining a count of packets that router n is sending to router r that are addressed to v or to a network on which v resides;

after based on the determined counts of packets of said neighbors n, determining the identity of the neighbor n of r that is the principal source of packets flowing to r that are addressed to v, continuing one node further upstream from the determined neighbor n of r that is the principal source of packets flowing to r that are addressed to v, and continuing to traceback through interconnected routers until a source of denial-of-service attack packets to v is determined or until further traceback is not possible; and

establishing a black hole host route to v as close as is possible to the source of the denial-of-service attack packets.

23. (Previously presented) The method as in claim 22, wherein the step of operating the traceback function operates the traceback function on a plurality of selected paths, wherein a particular path is selected based at least on an amount of traffic flowing through the path.